


# TECHNAXX®

For Your Digital Entertainment

*For Your Digital Entertainment*



Products Spring 2011

## Company Profile

### Technaxx Deutschland GmbH & Co.KG

---

Target of Technaxx Deutschland GmbH & Co.KG (est. 2003 in Frankfurt/Main-Germany, controlled by tenant) is to meet customer's demand by efficient and price orientated digital multimedia products, memory cards and USB sticks as well as licence products prompt and reliable.

End of 2010 Technaxx moved to a new office building with a larger stock department, not only to increase the company itself, but also to enlarge its product range. That's the basis for a stable and reliable customer retention. Stylish and frequently of futuristic design, easy-handling and high technical quality with a fair value for money are basis and guarantee for the future to be successful in both, domestic and foreign, entertainment and consumer electronics markets. The Technaxx product range always includes special developed products on basis of in-house design standard and performance in cooperation with qualified manufacturers of selected factories.

Decisive for a good market positioning as well as sales profit domestic and abroad verifies the correctness of this company idea. Moreover the whole Technaxx team brings in it's daily work many years of experience – from the technological and marketing side. Conclusion on that is high flexibility to react fast to changes on customer and market demands AND continual quality control and customer service are determinated as necessity.

The company's structure intentional is clear and lean (also to further expansion plans) to keep track on daily business – emphasised by the two company owners. In a nutshell: Technaxx customer's likes are the guiding principle for decisions in future, namely to provide state-of-the-art digital products in a high professional manner.





Made for  
 iPhone  iPad


## FMT-X4000



- FM frequency range: 87.5 ~ 108.0MHz (0.1 MHz steps / total 206 channels)
- Transmitting range: up to 10m
- Audio frequency range: 20 Hz - 20 KHz
- AUX Support: Line-in (audio entrance)
- AUX Input: 3.5mm (stereo jack)
- Power in: 12V ~ 24V (cigarette lighter jack)
- Power out: 5V (max. 2A)
- Charge external: \*Mini USB (socket)
- Weight device: total 316g

EAN: 4260101734846

# TECHNAXX®



## Video Memo VM-O 1 [Black]

- 300,000 pixel
- 128 x 160 display resolution
- 68° perspective
- 180mAh battery capacity
- 30 seconds time of recording
- < 0.5W power consumption
- Storage temperature -10°C up to 60°C
- Operating temperature 0°C up to 50°C
- 2 hours charging time
- Weight device: 45g
- Dimensions device: 67,98 (L) x 63,08 (W) x 11,48 mm (H)

EAN: 4260101735416 [Black] 4260101735393 [White]



## BT-Keyboard FLIP

- Universal wireless Bluetooth 2.0 connectivity
- Multiple functional keys
- Spill-proof silicone keyboard for optimal protection
- Magnetic clasp for secure handling
- Supports iPhone 4, iPad, Samsung Galaxy, Sony PS3, Symbian S60V3, Windows 6.0
- Broadcom 2042 chipset with wireless BT 2.0 interface
- Integrated iPhone 4 case
- Built-in Li-battery, rechargeable over Mini USB (operating time up to 40hrs.)
- Supports Windows 7, Vista, XP and MAC
- Dimensions device: 144 x 110 x 28mm

EAN: 4260101735331





## VIDEO WATCH ACTIONMASTER 4GB



- Video resolution: 640 \* 480; 30fps (frames per sec.)
- Photo resolution: 1600 \* 1200 (optional)
- Video format: AVI
- Photo format: JPG
- USB 1.1 (Hs)
- Flash memory: 4GB
- Li-battery, built-in
- Supports: Video recording function; Standard PC camera function (need to install the provided driver)
- Feature: Protected against water, dirt, dust, rain, snow
- OS: Windows Vista / XP / ME / 2000 / Mac OS 9.2.2 or higher version, no need to install a driver (Windows98 need a driver installation)


EAN: 4260101736390



## VIDEO WATCH COMPASS HD 4GB

- Video resolution: 1280 \* 720; 30fps (frames per sec.)
- Photo resolution: 1600 \* 1200 (optional)
- Video format: AVI
- Photo format: JPG
- USB 1.1 (Hs)
- Flash memory: 4GB

- Li-battery, built-in
- Supports: Video recording function; Compass function; Audio/Sound recording function; Standard PC camera function (need to install the provided driver)
- Feature: Protected against water, dirt, dust, rain, snow (with an extra waterproofed cap for the microphone button)
- OS: Windows Vista / XP / ME / 2000 / Mac OS 9.2.2 or higher version, no need to install a driver (Windows98 need a driver installation)



EAN: 4260101736406

## DigiTape DT-01



- Convert your old mix tapes and cassettes to MP3 to playback on iPods / MP3 players or burn to CD
- Plug & Play USB device (no driver required)
- Comes with Tape Converter software to guide you through transfer
- Audio output: listen on stereo, headphones or other speaker system

### Technical specifications:

- MP3 bit Rate: 64 – 320 kbps
- Audio output: 3.5mm stereo jack (headphones)
- Power: 3V (2x AA batteries) or USB connection
- Recommended duty cycle: 90 min. operation / 30 min. OFF
- Weight device: 170g
- Dimensions device: 113.1 (L) x 83.5 (W) x 30.3mm (H)

### System Requirements:

- Windows 7 / Vista / XP / 2000 / ME
- IBM PC/AT compatible computer with 800 MHz processor or higher
- Hard disc memory: 70 MB (for software), 4 GB (for audio editing)
- RAM 256 MB / CD ROM drive / USB interface



EAN: 4260101736468

## DigiScan DS-01



- Negative & slide scanner with 2.4" TFT LCD colour display
- Portable 5 megapixel scanner
- Supports USB 2.0 interface

### Technical specifications:

- 1/2.5" CMOS 5.17 Megapixel image sensor
- High resolution 1800dpi scanner
- Fix focus lens F/NO=6.4 / f=12.36mm
- Automatic color balance & exposure control
- Image capture resolution: 135 film/2544 x 1696 pixels (3:2) & 110 film/1088 x 816 pixels (4:3)
- 3 white LEDs light source back light
- Supports SD & SDHC memory cards
- Built-in hardware key for snapshot
- Power adaptor input 100 ~ 240V / 50 ~ 60Hz
- Power adaptor output 5V / 1A
- Connector: mini USB port
- Dimension device: 15.5 (H) x 11.4 (W) x 11.9 (L) cm



EAN: 4260101736475



## HDD DOCKING STATION SPEEDYSTORE USB 3.0

- Easy installation, 100% Plug & Play, hot-swappable
- Supports all 2.5"/3.5" SATA/II HDDs up to 2TB
- Supports USB 3.0 super-speed (5Gbps)
- Complies with USB 2.0 high speed (480Mbps)
- Complies USB 1.1 Low speed (1.5Mbps)
- 3in1 SD/MMC/MS card reader + USB 2.0 HOST
- OS: Windows7 / Vista / XP / 2000 / ME / 98SE / 98 / Mac OS 9.1 or above / Linux 2.4.X / AMD or Intel Pentium 133MHz or better
- Dimensions: 150mm (L) x 110mm (W) x 72mm (H)



EAN: 4260101734051



## SpeedyHUB 4-port USB 3.0


- Compliant to USB 3.0 specification revision 1.0
- Compatible with USB 2.0 specification
- Advanced technology allows optimal speeds when using multiple USB devices simultaneously
- Automatic status monitoring of power supply
- Active power supply
- Plug & Play function
- 4x USB Host (entrances) and 1x USB Slave/Client (exit)
- System Requirement: Desktop PC or notebook with USB port
- Operating systems (no driver needed): Windows 7, Vista, XP



EAN: 4260101734136



## USB 3.0 PCI-e CARD-302P



**USB 3.0**  
SUPER SPEED **5 Gb/s**



- PCI-e x1 Slot (for Desktop PC / Computer models)
- Two (2) Power LEDs
- NEC Chipset (built-in)
- Compatible with USB 3.0 and backwards with USB 2.0, 1.1, 1.0
- Supports 2 downstream ports for all speeds
- Each port provides DC 5V 1A via USB 3.0 connector
- USB ports are Hot Swapping compliant
- USB ports are Plug & Play compliant
- Fully compliant with USB 3.0 revision 1.0 specifications and INTEL xHCI rev. 0.96 specifications
- Supports USB data transfer rate of 5Gbps, 480Mbps, 12Mbps and 1.5Mbps
- Supports up to 127 USB devices connected to a single interface (requires additional USB Hubs to obtain this number)
- Supports OS: Windows7 / Vista / XP

EAN: 4260101734129



**USB 3.0**  
SUPER SPEED **5 Gb/s**



## USB 3.0 EXPRESS CARD-302E

- Express Slot (for Notebook / Laptop models)
- One (1) Power LED
- NEC Chipset (built-in)
- Compatible with USB 3.0 and backwards with USB 2.0, 1.1, 1.0
- Supports 2 downstream ports for all speeds
- Each port provides DC 5V 1A via USB 3.0 connector
- USB ports are Hot Swapping compliant
- USB ports are Plug & Play compliant
- Fully compliant with USB 3.0 revision 1.0 specifications and INTEL xHCI rev. 0.96 specifications
- Supports USB data transfer rate of 5Gbps, 480Mbps, 12Mbps and 1.5Mbps
- Supports up to 127 USB devices connected to a single interface (requires additional USB Hubs to obtain this number)
- Supports OS: Windows7 / Vista SP1 / XP

EAN: 4260101734112





## USB PRINT SERVER PS-01

- Easily connects your USB Printer to a network
- Allows multiple computers to share USB Printer on the network
- Print from any computer on your local network
- Supports DHCP Client and multiple network protocols
- 10Base-T/100Base-T auto-sensing
- Supports Web Management software
- Network interface: 10 / 100Mbps RJ45
- Network protocol: TCP / IP, LPR, DHCP
- Printer connection: USB 2.0, USB 1.1
- Management: Web Based-UI, Networking USB Utility
- Weight device: 35.5g

### System Requirements:

Windows 7, Vista, XP, 2003, 2000

Mac OS X 10.2 or later (only support LPR Printer)

Printer with a USB connection

EAN: 4260101735423

## USB Adapter to SATA and IDE



- SATA II (Serial ATA II): Version 1.0a compliant
- Dual-Head IDE Connector (40pin and 44pin) plus 1 SATA II Connector
- USB: Version 2.0 compliant; mass storage class bulk only transport specification compliant
- Operation with 1 IDE and 1 SATA HDD simultaneously
- "One Touch Backup" function
- Supports: Plug & Play; OTB function; IDE / SATA HDD 1TB, 2.5" / 3.5" HDD; 5.25" CD / DVD-ROM, CD-RW, COMBO, DVD-RW, DVD-RAM
- Data Transfer Rate: 480 Mb/s (max), 52x CD recording, 16x DVD recording
- External Power Supply: 100V ~ 240V AC, 50Hz / 60Hz
- Driver Software: Windows 98
- Supported Software: Windows 7 (32/64bit) / Vista / XP / ME / 2000 / Windows 98
- Weight device: 45g
- Dimensions device: 70 (L) x 45 (W) x 15mm (H)

EAN: 4260101736451

## Powerline Network Kit



- Universal power supply works within a voltage range of 100-240V AC, 50~60Hz
- Support QAM 256/64/16, DQPSK, DBPSK and ROBO modulation schemes
- Up to 85 Mbps data rate
- HomePlug Turbo 1.0 compatible
- 56-bit DES Link Encryption with key management
- Low power consumption

### Applications:

- Standard Video TV (SDTV) / TV over IP (IPTV) / Voice over IP calls (VOIP) / Shared broadband internet access / High speed broadband sharing / Audio and video streaming / PC file and application sharing, printer, game, cameras
- External Connectors: 1x Power jack und 1x 10/100M RJ45 Port

EAN: 4260101735409

## Wireless-N300 Power USB 2.0 Adapter



- Download music & movies, surf the internet and e-mail up to 5 times faster than previous generation wireless networks (Wireless 802.11g)
- Operating distance of up to 100m indoor and up to 300m in open space
- Data Security: 64/128-bit WEP Encryption, WPA, WPA-PSK, WPA2, WPA2-PSK, TKIP/AES
- Supports USB 2.0 interface, backward compatible to USB 1.1 and 1.0

### Technical Specifications:

- Wireless Standards: IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
- Host Interface: High speed USB 2.0 / 1.1 interface
- Data Rate: 802.11n: up to 300Mbps (Downlink) and 150Mbps (Uplink), 802.11g: 54 / 48 / 36 / 24 / 18 / 12 / 9 / 6 Mbps, 802.11b: 11 / 5.5 / 2 / 1 Mbps
- Frequency Band: 2.4GHz ISM Band
- Radio Channel: 1~14
- Antenna type: Screw-on Antenna
- RF Output Power: 25~27 dBm (Typical)
- Modulation: 11n: BPSK, QPSK, 16QAM, 64QAM mit OFDM, 11g: BPSK, QPSK, 16QAM, 64QAM, OFDM, 11b: DQPSK, DBPSK, DSSS, CCK

EAN: 4260101733788

## Router-3G Mobile WiFi-N



- WiFi N Router for 3G USB Modem (mobile use) or for DSL Modem/Cable Modem (home, office use)
- Automatic dialing, on-demand dialing, detachable time dialing etc.
- Supports PPPoE, Dynamic IP, and static IP broadband functions
- Supports UPnP, DDNS, static routing
- Supports SSID broadcast control and MAC access control list
- Supports 64/128/152-bit WEP, complies with 128 bit WPA/2 (TKIP/AES), MIC, IV Expansion, Shared Key Authentication, IEEE 802.1X
- Built-in firewall features IP, MAC, URL filtering which flexibly controls online access and time
- Built-in DHCP server with automatic dynamic IP address distribution
- User interface supports free WEB software updates as well as configuration file backup and restore
- Internal antenna
- Sleek exterior, can be mounted on a wall or placed horizontally on a table or desk

### Technical specifications

- Standards: IEEE 802.11n (Draft 2.0), IEEE 802.11g, IEEE 802.11b
- Wireless Signal Rates for 11n: 150/121.5/108/81/54/40.5/27/13.5Mbps, 130/117/104/78/52/39/26/13Mbps, 65/58.5/52/39/26/19.5/13/6.5Mbps
- Wireless Signal Rates for 11g: 54/48/36/24/18/12/9/6M (dynamic)
- Wireless signal rates for 11b: 11/5.5/2/1M (dynamic)
- Frequency range: 2.4 - 2.4835 GHz
- Wireless transmit power: 20dBm (MAX)
- Modulation technology: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM
- Receiver sensitivity: 130M: -68dBm@10% PER / 108M: -68dBm@10% PER / 54M: -68dBm@10% PER / 11M: -85dBm@8% PER / 6M: -88dBm@10% PER / 1M: -90dBm@8% PER
- Interface: 1x 10/100M Auto-Sensing RJ45 Port (LAN/WAN) & 1x USB 2.0 Port (for 3G card)

EAN: 4260101734471

## ROUTER-300 WiFi-N



### Features

- Supports PPPoE, Dynamic IP and static IP
- Automatic dialing, on-demand dialing and filling most dialing requirements
- Supports UPnP, DDNS, static routing
- Supports virtual server and DMZ options
- Supports SSID broadcast control and MAC access control list
- Supports 64/128/152bit WEP, complies with 128bit WPA/WPA2 standard (TKIP/AES), supports MIC, IV Expansion, Shared Key Authentication, IEEE 802.1X
- Built-in firewall features (IP, MAC, URL filtering) enable flexible online access control
- Built-in DHCP server with automatic IP address distribution
- User interface supports free WEB software updates
- Supports configuration file backup and restore
- 2 detachable Omni directional antennas
- The casing can be placed on a desk or mounted on a wall


### Technical specifications

- Standards: IEEE 802.11n (Draft 2.0), IEEE 802.11g, IEEE 802.11b
- Wireless signal rates for 11n: 270/243/216/162/108/81/54/27/13.5Mbps, 135/121.5/108/81/54/40.5/27/13.5Mbps, 130/117/104/78/52/39/26/13Mbps, 65/58.5/52/39/26/19.5/13/6.5Mbps
- Wireless signal rates for 11g: 54/48/36/24/18/12/9/6M (dynamic)
- Wireless signal rates for 11b: 11/5.5/2/1M (dynamic)
- Frequency range: 2.4 - 2.4835GHz
- Wireless transmit power: 20dBm (MAX)
- Modulation technology: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM
- Receiver sensitivity: 270M: -68dBm@10% PER / 130M: -68dBm@10% PER / 108M: -68dBm@10% PER / 54M: -68dBm@10% PER / 11M: -85dBm@8% PER / 6M: -88dBm@10% PER / 1M: -90dBm@8% PER
- Interface: 4+1 LAN 10/100M Auto-Sensing RJ45 Ports
- Antenna: 3dBi Omni Directional Antenna x 2

EAN: 4260101734464



# Protection Jacket **Black**



Made for  
**iPad**



- Robust, shock-proof protective bag with inside compartments, carry handle and outer pocket
- Suits the iPad
- Hinged with full access to the iPad
- Stand-up box, in order to use as iPad monitor
- Hand rest, soft and hinged
- Perfect for presentations, business meetings and travelling

EAN: 4260101734693

# Leather Power Case -TE04



Made for  
**iPhone**

- Compatibility: iPhone 3GS und iPhone 3G
- Battery: Li-Polymer
- Capacity: 1500mAh
- Output: DC 5V 500mA
- Stand-by time: up to 300 hours
- Talking time: up to 5 hours
- Internet use - iPhone: up to 5 hours
- Internet use - on WiFi/WLAN: up to 5.5 hours
- Audio Play: up to 20 hours
- Video Play: up to 6 hours
- Game Play: up to 3 hours
- eMail: up to 6 hours
- Size / Weight: 65 x 135 x 25mm / 90 g

## Package Contents:

- Leather Power Case-TE04
- USB micro cable
- User Manual

EAN: 4260101734853

# iPad Car & Carry Kit



Made for  
**iPad**

- Very secure fixing of the holder to the headrest of the vehicle
- Precise adjustment of the iPad holder through a rotatable and pivotable arm
- Keep the iPad clean and steady in position with full access to the iPad
- Includes protection bag for the iPad
- Connect and disconnect the iPad from the holder easily
- Gives even more possible fields of application for the iPad



## Package Contents:

- iPad Car & Carry Kit
- iPad Stand
- Bag for the iPad holder
- Nuts & bolts
- User Manual

EAN: 4260101735119

# TECHNAXX®



## FMT 100

EAN: 4260101731531 • Supports SD cards and has one USB and Audio interface to connect MP3 and MP4 devices

- Supports MP3 and WMA format
- Reads files from SD card and USB interface directly
- LED Display; shows frequency information

• Full frequency range (87.7 – 107.9 MHz)

• Saves frequency and music title

• Secure transmitter power and frequency transfer

• Rotatable axis for easy use

• Modern and stylish design

• Device starts with the last saved parameter for frequency, volume and titel number



EAN: 4260101731531



## FMT 200BT

• Supports SD cards and has one USB and Audio interface to connect MP3- / MP4 devices

• Audio-in-port for external audio devices (DVD, MP3, Playstation)

• Full frequency range (87.7 – 108.0 MHz)

• Saves frequency and music title

• Modern and stylish design

• Device starts with the last saved parameter for frequency, volume and titel number

• Built-in microphone

• Telephone mode



EAN: 426010173180 7



## FMT 300BT

- Bluetooth for the car, compatible with nearly all Bluetooth mobile phones
- CVC-technology for clearly speaking (restrain noise & echo)
- Priorität: Bluetooth call à Bluetooth music à Line-in à SD/USB

• Plays music from mobile phone via Bluetooth

• Re-dial function\* & voice-dial function\* (\* depend on mobile phone functions)

• Steering wheel remote control – simple & safe while driving and hand remote control

• Flexible, rotatable axis of device easily operated



EAN: 426010173222 4



## Kids TV-Remote Control

- You control what your child watches on TV!
- 8 keys to program your wish
- Child-friendly TV viewing experience
- Easiest handling for kids



- Keys: 8 pcs.
- IR Distance: 8-10 meters
- Carry frequency: 10-120K KHz, up to 360 bits long
- Batteries: 2 X AAA Alkaline (SUM-4)
- Power consumption -> operation current: 50mA (MAX)
- Power consumption -> standby current: less than 10 µA
- Dimensions (W x H x D): 61.7 x 68.5 x 41.9 mm
- Weight(without batteries): 63.5 g

EAN: 4260101735003



[www.nickelodeon.tv](http://www.nickelodeon.tv)

© 2010 Viacom International Inc. All Rights Reserved. Nickelodeon, SpongeBob SquarePants and all related titles, logos and characters are trademarks of Viacom International Inc. Created by Stephen Hillenburg.

# TECHNAXX®

For Your Digital Entertainment

[www.technaxx-europe.de](http://www.technaxx-europe.de)

[www.technaxx.de](http://www.technaxx.de)

## Technaxx Germany Head Office

Kruppstraße 105  
60388 Frankfurt/Main  
Germany

Phone: +49 (0) 69 - 90 47 552-0

Fax: +49 (0) 69 - 90 47 552-16

E-Mail: [verkauf@technaxx.de](mailto:verkauf@technaxx.de)

E-Mail: [sale@technaxx.com](mailto:sale@technaxx.com)

## Technaxx Office Italia

Via Federici  
Galleria Mimosa  
61100 Pesaro (PU)

Tel: +39 (0)721-27 05 60

Fax: +39 (0)721-27 99 34

E-Mail: [info@technaxx.it](mailto:info@technaxx.it)